
gcovr Documentation

Release 4.0

the gcovr authors

Mar 14, 2019

Contents:

1	Installation	3
2	Gcovr User Guide	5
2.1	Getting Started	6
2.2	The gcovr Command	10
2.3	Using Filters	13
2.4	Acknowledgements	14
3	Contributing	15
3.1	How to report bugs	15
3.2	How to help	15
3.3	How to submit a Pull Request	16
3.4	How to set up a development environment	16
3.5	Project Structure	17
3.6	Test suite	17
3.7	Become a gcovr developer	18
4	Change Log	19
4.1	4.0 (17 July 2018)	19
4.2	3.4 (12 February 2018)	20
4.3	3.3 (6 August 2016)	20
4.4	3.2 (5 July 2014)	21
4.5	3.1 (6 December 2013)	21
4.6	3.0 (10 August 2013)	21
4.7	2.4 (13 April 2012)	22
4.8	2.3.1 (6 January 2012)	22
4.9	2.3 (11 December 2011)	22
4.10	2.2 (10 December 2011)	22
4.11	2.1 (26 November 2010)	23
4.12	2.0 (22 August 2010)	23
5	License	25

Gcovr provides a utility for managing the use of the GNU [gcov](#) utility and generating summarized code coverage results. This command is inspired by the Python [coverage.py](#) package, which provides a similar utility for Python.

The `gcovr` command can produce different kinds of coverage reports:

- `default`: compact human-readable summaries
- `--xml`: machine readable XML reports in [Cobertura](#) format
- `--html`: HTML summaries
- `--html-details`: HTML report with annotated source files

Thus, `gcovr` can be viewed as a command-line alternative to the `lcov` utility, which runs `gcov` and generates an HTML-formatted report. The development of `gcovr` was motivated by the need for text summaries and XML reports.

Quick Links

- Getting Help
 - [Submit a ticket](#)
 - [Stack Overflow](#)
 - [Chat on Gitter](#)
 - Install from PyPI: `pip install gcovr`
 - [Source Code on GitHub](#)
 - [Change Log](#)
-

CHAPTER 1

Installation

Gcovr is available as a Python package that can be installed via `pip`.

Install newest stable `gcovr` release from PyPI:

```
pip install gcovr
```

Install development version from GitHub:

```
pip install git+https://github.com/gcovr/gcovr.git
```

Which environments does `gcovr` support?

- Python: 2.7 and 3.4+.

The automated tests run on CPython 2.7, 3.4, and 3.5, and PyPy 2.7 and 3.5.

Python 2.6 is no longer supported. The last stable release for that Python version was 3.4.

- Operating System: Linux, Windows, and macOS.

The automated tests run on Ubuntu 14.04 and Windows Server 2012.

- Compiler: GCC and Clang.

The automated tests run on GCC 5.

Gcovr provides a utility for managing the use of the GNU `gcov` utility and generating summarized code coverage results. This command is inspired by the Python `coverage.py` package, which provides a similar utility for Python.

The `gcovr` command can produce different kinds of coverage reports:

- `default`: compact human-readable summaries
- `--xml`: machine readable XML reports in Cobertura format
- `--html`: HTML summaries
- `--html-details`: HTML report with annotated source files

Thus, `gcovr` can be viewed as a command-line alternative to the `lcov` utility, which runs `gcov` and generates an HTML-formatted report. The development of `gcovr` was motivated by the need for text summaries and XML reports.

The [Gcovr Home Page](http://gcovr.com) is <http://gcovr.com>. Automated test results are available through [Travis CI](#) and [Appveyor](#). Gcovr is available under the [BSD license](#).

This documentation describes Gcovr 4.0.

This User Guide provides the following sections:

- *Getting Started*
 - *Tabular Output of Code Coverage*
 - *Tabular Output of Branch Coverage*
 - *XML Output*
 - *HTML Output*
- *The gcovr Command*
 - *gcovr*
- *Using Filters*

– *Filters for symlinks*

- *Acknowledgements*

Related documents:

- *Installation*
- *Contributing* (includes instructions for bug reports)
- *Change Log*
- *License*

2.1 Getting Started

The `gcovr` command provides a summary of the lines that have been executed in a program. Code coverage statistics help you discover untested parts of a program, which is particularly important when assessing code quality. Well-tested code is a characteristic of high quality code, and software developers often assess code coverage statistics when deciding if software is ready for a release.

The `gcovr` command can be used to analyze programs compiled with GCC. The following sections illustrate the application of `gcovr` to test coverage of the following program:

```
1 // example.cpp
2
3 int foo(int param)
4 {
5     if (param)
6     {
7         return 1;
8     }
9     else
10    {
11        return 0;
12    }
13 }
14
15 int main(int argc, char* argv[])
16 {
17     foo(0);
18
19     return 0;
20 }
```

This code executes several subroutines in this program, but some lines in the program are not executed.

2.1.1 Tabular Output of Code Coverage

We compile `example1.cpp` with the GCC compiler as follows:

```
g++ -fprofile-arcs -ftest-coverage -fPIC -O0 example.cpp -o program
```

Note that we compile this program without optimization, because optimization may combine lines of code and otherwise change the flow of execution in the program. Additionally, we compile with the `-fprofile-arcs`

`-ftest-coverage` `-fPIC` compiler options, which add logic to generate output files that can be processed by the `gcov` command.

The compiler generates the `program` executable. When we execute this command:

```
./program
```

the files `example1.gcno` and `example1.gda` are generated. These files are processed with by `gcov` to generate code coverage statistics. The `gcovr` command calls `gcov` and summarizes these code coverage statistics in various formats. For example:

```
gcovr -r .
```

generates a text summary of the lines executed:

```
-----
                        GCC Code Coverage Report
Directory: .
-----
File                               Lines   Exec  Cover  Missing
-----
example.cpp                         7       6   85%    7
TOTAL                               7       6   85%
```

Each line of this output includes a summary for a given source file, including the number of lines instrumented, the number of lines executed, the percentage of lines executed, and a summary of the line numbers that were not executed. To improve clarity, `gcovr` uses an aggressive approach to grouping uncovered lines and will combine uncovered lines separated by “non-code” lines (blank, freestanding braces, and single-line comments) into a single region. As a result, the number of lines listed in the “Missing” list may be greater than the difference of the “Lines” and “Exec” columns.

The `-r` option specifies the root directory for the files that are being analyzed. This allows `gcovr` to generate a simpler report (without absolute path names), and it allows system header files to be excluded from the analysis.

Note that `gcov` accumulates statistics by line. Consequently, it works best with a programming style that places only one statement on each line.

2.1.2 Tabular Output of Branch Coverage

The `gcovr` command can also summarize branch coverage using the `--branches` option:

```
gcovr -r . --branches
```

This generates a tabular output that summarizes the number of branches, the number of branches taken and the branches that were not completely covered:

```
-----
                        GCC Code Coverage Report
Directory: .
-----
File                               Branches  Taken  Cover  Missing
-----
example.cpp                         2         1   50%    5
TOTAL                               2         1   50%
```

2.1.3 XML Output

The default output format for `gcovr` is to generate a tabular summary in plain text. The `gcovr` command can also generate an XML output using the `--xml` and `--xml-pretty` options:

```
gcovr -r . --xml-pretty
```

This generates an XML summary of the lines executed:

```
<?xml version="1.0" ?>
<!DOCTYPE coverage
  SYSTEM 'http://cobertura.sourceforge.net/xml/coverage-04.dtd'>
<coverage branch-rate="0.5" branches-covered="1" branches-valid="2"
  complexity="0.0" line-rate="0.8571428571428571" lines-covered="6"
  lines-valid="7" timestamp="1529246640" version="gcovr 4.0">
  <sources>
    <source>.</source>
  </sources>
  <packages>
    <package branch-rate="0.5" complexity="0.0" line-rate="0.8571428571428571"
      name="">
      <classes>
        <class branch-rate="0.5" complexity="0.0" filename="example.cpp"
          line-rate="0.8571428571428571" name="example_cpp">
          <methods/>
          <lines>
            <line branch="false" hits="1" number="3"/>
            <line branch="true" condition-coverage="50% (1/2)" hits="1" number="5">
              <conditions>
                <condition coverage="50%" number="0" type="jump"/>
              </conditions>
            </line>
            <line branch="false" hits="0" number="7"/>
            <line branch="false" hits="1" number="11"/>
            <line branch="false" hits="1" number="15"/>
            <line branch="false" hits="1" number="17"/>
            <line branch="false" hits="1" number="19"/>
          </lines>
        </class>
      </classes>
    </package>
  </packages>
</coverage>
```

This XML format is in the [Cobertura XML](#) format suitable for import and display within the [Jenkins](#) and [Hudson](#) continuous integration servers using the [Cobertura Plugin](#).

The `--xml` option generates a denser XML output, and the `--xml-pretty` option generates an indented XML output that is easier to read. Note that the XML output contains more information than the tabular summary. The tabular summary shows the percentage of covered lines, while the XML output includes branch statistics and the number of times that each line was covered. Consequently, XML output can be used to support performance optimization in the same manner that `gcov` does.

2.1.4 HTML Output

The `gcovr` command can also generate a simple HTML output using the `--html` option:

```
gcovr -r . --html -o example-html.html
```

This generates a HTML summary of the lines executed. In this example, the file `example1.html` is generated, which has the following output:

GCC Code Coverage Report

Directory: .	Exec Total Coverage			
Date: 2018-06-17 17:13:15	Lines:	6	7	85.7 %
Legend: low: < 75.0 % medium: >= 75.0 % high: >= 90.0 %	Branches:	1	2	50.0 %

File	Lines	85.7 %	6 / 7	Branches	50.0 %	1 / 2
<code>example.cpp</code>	<div style="width: 85.7%; height: 10px; background-color: yellow;"></div>					

Generated by: [GCOVR \(Version 4.0\)](#)

The default behavior of the `--html` option is to generate HTML for a single webpage that summarizes the coverage for all files. The HTML is printed to standard output, but the `-o` (`--output`) option is used to specify a file that stores the HTML output.

The `--html-details` option is used to create a separate web page for each file. Each of these web pages includes the contents of file with annotations that summarize code coverage. Consider the following command:

```
gcovr -r . --html --html-details -o example-html-details.html
```

This generates the following HTML page for the file `example1.cpp`:

GCC Code Coverage Report

Directory: .	Exec	Total	Coverage
File: example.cpp	Lines: 6	7	85.7 %
Date: 2018-06-17 17:13:15	Branches: 1	2	50.0 %

Line	Branch	Exec	Source
1			// example.cpp
2			
3		1	int foo(int param)
4			{
5	x✓	1	if (param)
6			{
7			return 1;
8			}
9			else
10			{
11		1	return 0;
12			}
13			}
14			
15		1	int main(int argc, char* argv[])
16			{
17		1	foo(0);
18			
19		1	return 0;
20			}
21			

Generated by: [GCOVR \(Version 4.0\)](#)

Note that the `--html-details` option can only be used with the `-o` (`--output`) option. For example, if the `--output` option specifies the output file `coverage.html`, then the web pages generated for each file will have names of the form `coverage.<filename>.html`.

2.2 The gcovr Command

The `gcovr` command recursively searches a directory tree to find `gcov` coverage files, and generates a text summary of the code coverage. The `--help` option generates the following summary of the `gcovr` command line options:

2.2.1 gcovr

A utility to run `gcov` and summarize the coverage in simple reports.

```
usage: gcovr [options] [search_paths...]
```

See <http://gcovr.com/> for the full manual.

Options

search_paths

Search these directories for coverage files. Defaults to `-root` and `-object-directory`.

-h, --help

Show this help message, then exit.

--version

Print the version number, then exit.

-v, --verbose

Print progress messages. Please include this output in bug reports.

-r <root>, --root <root>

The root directory of your source files. Defaults to `'.'`, the current directory. File names are reported relative to this root. The `-root` is the default `-filter`.

--fail-under-line <min>

Exit with a status of 2 if the total line coverage is less than MIN. Can be ORed with exit status of `'-fail-under-branch'` option.

--fail-under-branch <min>

Exit with a status of 4 if the total branch coverage is less than MIN. Can be ORed with exit status of `'-fail-under-line'` option.

--source-encoding <source_encoding>

Select the source file encoding. Defaults to the system default encoding (UTF-8).

--html-medium-threshold <medium>

If the coverage is below MEDIUM, the value is marked as low coverage in the HTML report. MEDIUM has to be lower than or equal to value of `-html-high-threshold`. If MEDIUM is equal to value of `-html-high-threshold` the report has only high and low coverage. Default is 75.0.

--html-high-threshold <high>

If the coverage is below HIGH, the value is marked as medium coverage in the HTML report. HIGH has to be greater than or equal to value of `-html-medium-threshold`. If HIGH is equal to value of `-html-medium-threshold` the report has only high and low coverage. Default is 90.0.

Output Options

Gcovr prints a text report by default, but can switch to XML or HTML.

-o <output>, --output <output>

Print output to this filename. Defaults to stdout. Required for `-html-details`.

-b, --branches

Report the branch coverage instead of the line coverage. For text report only.

-u, --sort-uncovered

Sort entries by increasing number of uncovered lines. For text and HTML report.

-p, --sort-percentage

Sort entries by increasing percentage of uncovered lines. For text and HTML report.

-x, --xml

Generate a Cobertura XML report.

--xml-pretty

Pretty-print the XML report. Implies `-xml`. Default: False.

- html**
Generate a HTML report.
- html-details**
Add annotated source code reports to the HTML report. Requires `-output` as a basename for the reports. Implies `-html`.
- html-title** <title>
Use TITLE as title for the HTML report. Default is Head.
- html-absolute-paths**
Use absolute paths to link the `-html-details` reports. Defaults to relative links.
- html-encoding** <html_encoding>
Override the declared HTML report encoding. Defaults to UTF-8. See also `-source-encoding`.
- s, --print-summary**
Print a small report to stdout with line & branch percentage coverage. This is in addition to other reports. Default: False.

Filter Options

Filters decide which files are included in the report. Any filter must match, and no exclude filter must match. A filter is a regular expression that matches a path. Filter paths use forward slashes, even on Windows.

- f** <filter>, **--filter** <filter>
Keep only source files that match this filter. Can be specified multiple times. If no filters are provided, defaults to `-root`.
- e** <exclude>, **--exclude** <exclude>
Exclude source files that match this filter. Can be specified multiple times.
- gcov-filter** <gcov_filter>
Keep only gcov data files that match this filter. Can be specified multiple times.
- gcov-exclude** <gcov_exclude>
Exclude gcov data files that match this filter. Can be specified multiple times.
- exclude-directories** <exclude_dirs>
Exclude directories that match this regex while searching raw coverage files. Can be specified multiple times.

GCOV Options

The ‘gcov’ tool turns raw coverage files (`.gda` and `.gno`) into `.gcov` files that are then processed by `gcovr`. The `gno` files are generated by the compiler. The `gda` files are generated when the instrumented program is executed.

- gcov-executable** <gcov_cmd>
Use a particular gcov executable. Must match the compiler you are using, e.g. ‘`llvm-cov gcov`’ for Clang. Can include additional arguments. Defaults to the GCOV environment variable, or ‘gcov’: ‘gcov’.
- exclude-unreachable-branches**
Exclude branch coverage with LCOV/GCOV exclude markers. Additionally, exclude branch coverage from lines without useful source code (often, compiler-generated “dead” code). Default: False.
- g, --use-gcov-files**
Use existing gcov files for analysis. Default: False.
- gcov-ignore-parse-errors**
Skip lines with parse errors in GCOV files instead of exiting with an error. A report will be shown on stderr. Default: False.

--object-directory <objdir>

Override normal working directory detection. Gcovr needs to identify the path between gcda files and the directory where the compiler was originally run. Normally, gcovr can guess correctly. This option specifies either the path from gcc to the gcda file (i.e. gcc's '-o' option), or the path from the gcda file to gcc's working directory.

-k, --keep

Keep gcov files after processing. This applies both to files that were generated by gcovr, or were supplied via the `--use-gcov-files` option. Default: False.

-d, --delete

Delete gcda files after processing. Default: False.

-j <gcov_parallel>

Set the number of threads to use in parallel.

The above *Getting Started* guide illustrates the use of some command line options. *Using Filters* is discussed below.

2.3 Using Filters

Gcovr tries to only report coverage for files within your project, not for your libraries. This is influenced by the following options:

- `-r, --root`
- `-f, --filter`
- `-e, --exclude`
- `--gcov-filter`
- `--gcov-exclude`
- `--exclude-directories`
- (the current working directory where gcovr is invoked)

These options take filters. A filter is a regular expression that matches a file path. Because filters are regexes, you will have to escape "special" characters with a backslash `\`.

Always use forward slashes `/` as path separators, even on Windows:

- wrong: `--filter C:\project\src\`
- correct: `--filter C:/project/src/`

If the filter looks like an absolute path, it is matched against an absolute path. Otherwise, the filter is matched against a relative path, where that path is relative to the current directory. Examples of relative filters:

- `--filter subdir/` matches only that subdirectory
- `--filter '\.\./src/'` matches a sibling directory `../src`. But because a dot `.` matches any character in a regex, we have to escape it. You have to use additional shell escaping. This example uses single quotes for Bash or POSIX shell.
- `--filter '(./+)?foo\.c$'` matches only files called `foo.c`. The regex must match from the start of the relative path, so we ignore any leading directory parts with `(./+)?`. The `$` at the end ensures that the path ends here.

If no `--filter` is provided, the `--root` is turned into a default filter. Therefore, files outside of the `--root` directory are excluded.

To be included in a report, the source file must match any `--filter`, and must not match any `--exclude` filter.

The `--gcov-filter` and `--gcov-exclude` filters apply to the `.gcov` files created by `gcov`. This is useful mostly when running `gcov` yourself, and then invoking `gcovr` with `-g/--use-gcov-files`. But these filters also apply when `gcov` is launched by `gcovr`.

2.3.1 Filters for symlinks

Gcovr matches filters against *real paths* that have all their symlinks resolved. E.g. consider this project layout:

```
/home/you/
├── project/ (pwd)
│   ├── src/
│   ├── relevant-library/ -> ../external-library/
│   └── ignore-this/
└── external-library/
    └── src/
```

Here, the `relevant-library` has the real path `/home/you/external-library`.

To write a filter that includes both `src/` and `relevant-library/src/`, we cannot use `--filter relevant-library/src/` because that contains a symlink. Instead, we have to use an absolute path to the real name:

```
gcovr --filter src/ --filter /home/you/external-library/src/
```

or a relative path to the real path:

```
gcovr --filter src/ --filter '\.\./external-library/src/'
```

Note: This section discusses symlinks on Unix systems. The behavior under Windows is unclear. If you have more insight, please update this section by submitting a pull request (see our [contributing guide](#)).

2.4 Acknowledgements

Gcovr is maintained by:

William Hart, John Siirola, and Lukas Atkinson.

The following developers contributed to `gcovr` (ordered alphabetically):

Andrew Stone, Arvin Schnell, Attie Grande, Bernhard Breinbauer, Carlos Jenkins, Christian Taedcke, Dave George, Dom Postorivo, goriy, jallison, James Reynolds, Jessica Levine, Joel Klinghed, John Siirola, Jörg Kreuzberger, Kai Blaschke, Kevin Cai, libPhipp, Lukas Atkinson, Luke Woydziak, Martin Mraz, Matsumoto Taichi, Matthias Schmieder, Matthieu Darbois, Michał Pszona, Michael Förderer, Mikael Salson, Mikk Leini, Nikolaj Schumacher, Piotr Dziwinski, Reto Schneider, Robert Rosengren, Songmin Li, Steven Myint, Sylvestre Ledru, trapzero, William Hart, and possibly others.

The development of Gcovr has been partially supported by Sandia National Laboratories. Sandia National Laboratories is a multi-program laboratory managed and operated by Sandia Corporation, a wholly owned subsidiary of Lockheed Martin Corporation, for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-AC04-94AL85000.

This document contains:

- our *guidelines for bug reports*
- *general contribution guidelines*
- a *checklist for pull requests*
- a developer guide that explains the *development environment, project structure, and test suite*

3.1 How to report bugs

When reporting a bug, first [search our issues](#) to avoid duplicates. In your bug report, please describe what you expected gcovr to do, and what it actually did. Also try to include the following details:

- how you invoked gcovr, i.e. the exact flags and from which directory
- your project layout
- your gcovr version
- your compiler version
- your operating system
- and any other relevant details.

Ideally, you can provide a short script and the smallest possible source file to reproduce the problem.

3.2 How to help

If you would like to help out, please take a look at our [open issues](#) and [pull requests](#). The issues labeled [help wanted](#) and [needs review](#) would have the greatest impact.

There are many ways how you can help:

- assist other users with their problems
- share your perspective as a gcovr user in discussions
- test proposed changes in your real-world projects
- improve our documentation
- submit pull requests with bug fixes and enhancements

3.3 How to submit a Pull Request

Thank you for helping with gcovr development! Please follow this checklist for your pull request:

- **Is this a good approach?** Fixing open issues is always welcome! If you want to implement an enhancement, please discuss it first as a GitHub issue.
- **Does it work?** Please run the tests locally:

```
python -m pytest
```

In any case, the tests will run automatically when you open the pull request. But please prevent unnecessary build failures and run the tests yourself first. If you cannot run the tests locally, you can activate Travis CI or Appveyor for your fork.

If you add new features, please try to add a test case.

- **Does it conform to the style guide?** The source code should conform to the [PEP 8](#) standard. Please check your code:

```
python -m flake8 doc gcovr --ignore E501
```

- **Add yourself as an author.** If this is your first contribution to gcovr, please add yourself to the `AUTHORS.txt` file.
- **One change at a time.** Please keep your commits and your whole pull request fairly small, so that the changes are easy to review. Each commit should only contain one kind of change, e.g. refactoring *or* new functionality.
- **Why is this change necessary?** When you open the PR, please explain why we need this change and what your PR does. If this PR fixes an open issue, reference that issue in the pull request description.

Once you submit the PR, it will be automatically tested on Windows and Linux, and code coverage will be collected. Your code will be reviewed. This can take a week. Please fix any issues that are discovered during this process. Feel free to force-push your updates to the pull request branch.

If you need assistance for your pull request, you can

- chat in [our Gitter room](#)
- discuss your problem in an issue
- open an unfinished pull request as a work in progress (WIP), and explain what you've like to get reviewed

3.4 How to set up a development environment

- (Optional) Fork the project on GitHub.
- Clone the git repository.
- (Optional) Set up a virtualenv.

- Install gcovr in development mode, and install the test requirements:

```
pip install -e .
pip install -r requirements.txt
```

You can then run gcovr as `gcovr` or `python -m gcovr`.

Run the tests to verify that everything works (see below).

- (Optional) Install documentation requirements:

```
pip install -r doc/requirements.txt
```

See `doc/README.txt` for details on working with the documentation.

- (Optional) Activate Travis and Appveyor for your forked GitHub repository, so that the cross-platform compatibility tests get run whenever you push your work to your repository. These tests will also be run when you open a pull request to the main gcovr repository.

Tip: If you have problems getting everything set up, consider looking at the `.travis.yml` (Linux) and `appveyor.yml` (Windows) files.

On **Windows**, you will need to install a GCC toolchain as the tests expect a Unix-like environment. You can use MinGW-W64 or MinGW. To run the tests, please make sure that the `make` and `cmake` from your MinGW distribution are in the system `PATH`.

3.5 Project Structure

Path	Description
/	project root
/gcovr/	the gcovr source code (Python module)
/gcovr/__main__.py	command line interface + top-level behaviour
/gcovr/templates/	HTML report templates
/gcovr/tests/	unit tests + integration test corpus
/setup.py	Python package configuration
/doc/	documentation
/doc/sources/	user guide + website
/doc/examples/	runnable examples for the user guide

The program entrypoint and command line interface is in `gcovr/__main__.py`. The coverage data is parsed in the `gcovr.gcov` module. The HTML, XML, text, and summary reports are in `gcovr.html_generator` and respective modules.

3.6 Test suite

The tests are in the `gcovr/tests` directory. You can run the tests with `python -m pytest`.

There are unit tests for some parts of gcovr, and a comprehensive corpus of example projects that are executed as the `test_gcovr.py` test. Each `gcovr/tests/*` directory is one such example project.

Each project in the corpus contains a `Makefile` and a `reference` directory. The `Makefile` controls how the project is built, and how gcovr should be invoked. The `reference` directory contains baseline files against which the gcovr output is compared. Each project is tested three times to cover `txt`, `html`, and `xml` output.

Because the tests are a bit slow, you can limit the tests to a specific test file, example project, or output format. For example:

```
# run only XML tests
python -m pytest -k xml

# run the simple1 tests
python -m pytest -k simple1

# run the simple1 tests only for XML
python -m pytest -k 'xml and simple1'
```

To see all tests, run `pytest` in `-v` verbose mode. To see which tests would be run, add the `--collect-only` option.

The tests currently assume that you are using GCC 5.

3.7 Become a gcovr developer

After you've contributed a bit (whether with discussions, documentation, or code), consider becoming a gcovr developer. As a developer, you can:

- manage issues and pull requests (label and close them)
- review pull requests (a developer must approve each PR before it can be merged)
- participate in votes

Just open an issue that you're interested, and we'll have a quick vote.

gcovr Release History and Change Log

4.1 4.0 (17 July 2018)

Breaking changes:

- This release drops support for Python 2.6. (#250)
- PIP is the only supported installation method.
- No longer encoding-agnostic under Python 2.7. If your source files do not use the system encoding (probably UTF-8), you will have to specify a `--source-encoding`. (#148, #156, #256)
- Filters now use forward slashes as path separators, even on Windows. (#191, #257)
- Filters are no longer normalized into pseudo-paths. This could change the interpretation of filters in some edge cases.

Improvements and new features:

- Improved `--help` output. (#236)
- Parse the GCC 8 gcov format. (#226, #228)
- New `--source-encoding` option, which fixes decoding under Python 3. (#256)
- New `--gcov-ignore-parse-errors` flag. By default, gcovr will now abort upon parse errors. (#228)
- Detect the error when gcov cannot create its output files (#243, #244)
- Add `-j` flag to run gcov processes in parallel. (#3, #36, #239)
- The `--html-details` flag now implies `--html`. (#93, #211)
- The `--html` output can now be used without an `--output` filename (#223)
- The docs are now managed with Sphinx. (#235, #248, #249, #252, #253)

- New `-html-title` option to change the title of the HTML report. (#261, #263)
- New options `-html-medium-threshold` and `-html-high-threshold` to customize the color legend. (#261, #264)

Internal changes:

- Huge refactoring. (#214, #215, #221 #225, #228, #237, #246)
- Various testing improvements. (#213, #214, #216, #217, #218, #222, #223, #224, #227, #240, #241, #245)
- HTML reports are now rendered with Jinja2 templates. (#234)
- New contributing guide. (#253)

4.2 3.4 (12 February 2018)

- Added `-html-encoding` command line option (#139).
- Added `-fail-under-line` and `-fail-under-branch` options, which will error under a given minimum coverage. (#173, #116)
- Better pathname resolution heuristics for `-use-gcov-file`. (#146)
- The `-root` option defaults to current directory `'.'`.
- Improved reports for `“(“`, `“(“`, `“(“` lines.
- HTML reports show full timestamp, not just date. (#165)
- HTML reports treat 0/0 coverage as NaN, not 100% or 0%. (#105, #149, #196)
- Add support for coverage-04.dtd Cobertura XML format (#164, #186)
- Only Python 2.6+ is supported, with 2.7+ or 3.4+ recommended. (#195)
- Added CI testing for Windows using Appveyor. (#189, #200)
- Reports use forward slashes in paths, even on Windows. (#200)
- Fix to support filtering with absolute paths.
- Fix HTML generation with Python 3. (#168, #182, #163)
- Fix `-html-details` under Windows. (#157)
- Fix filters under Windows. (#158)
- Fix verbose output when using existing gcov files (#143, #144)

4.3 3.3 (6 August 2016)

- Added CI testing using TravisCI
- Added more tests for out of source builds and other nested builds
- Avoid common file prefixes in HTML output (#103)
- Added the `-exclude-directories` argument to exclude directories from the search for symlinks (#87)
- Added branches taken/not taken to HTML (#75)
- Use `-object-directory` to scan for gcov data files (#72)
- Improved logic for nested makefiles (#135)

- Fixed unexpected semantics with `-root` argument (#108)
- More careful checks for covered lines (#109)

4.4 3.2 (5 July 2014)

- Adding a test for out of source builds
- Using the starting directory when processing gcov filenames. (#42)
- Making relative paths the default in html output.
- Simplify html bar with coverage is zero.
- Add option for using existing gcov files (#35)
- Fixing `-root` argument processing (#27)
- Adding logic to cover branches that are ignored (#28)

4.5 3.1 (6 December 2013)

- Change to make the `-r/-root` options define the root directory for source files.
- Fix to apply the `-p` option when the `-html` option is used.
- Adding new option, `'-exclude-unreachable-branches'` that will exclude branches in certain lines from coverage report.
- Simplifying and standardizing the processing of linked files.
- Adding tests for deeply nested code, and symbolic links.
- Add support for multiple `—filter` options in same manner as `—exclude` option.

4.6 3.0 (10 August 2013)

- Adding the `'-gcov-executable'` option to specify the name/location of the gcov executable. The command line option overrides the environment variable, which overrides the default `'gcov'`.
- Adding an empty `"<methods/>"` block to `<classes/>` in the XML output: this makes out XML compliant with the Cobertura DTD. (#3951)
- Allow the GCOV environment variable to override the default `'gcov'` executable. The default is to search the PATH for `'gcov'` if the GCOV environment variable is not set. (#3950)
- Adding support for LCOV-style flags for excluding certain lines from coverage analysis. (#3942)
- Setup additional logic to test with Python 2.5.
- Added the `-html` and `-html-details` options to generate HTML.
- Sort output for XML to facilitate baseline tests.
- Added error when the `-object-directory` option specifies a bad directory.
- Added more flexible XML testing, which can ignore XML elements that frequently change (e.g. timestamps).
- Added the `'—xml-pretty'` option, which is used to generate pretty XML output for the user manual.

- Many documentation updates

4.7 2.4 (13 April 2012)

- New approach to walking the directory tree that is more robust to symbolic links (#3908)
- Normalize all reported path names
 - Normalize using the full absolute path (#3921)
 - Attempt to resolve files referenced through symlinks to a common project-relative path
- Process `gcno` files when there is no corresponding `gcda` file to provide coverage information for unexecuted modules (#3887)
- Windows compatibility fixes
 - Fix for how we parse `source:` file names (#3913)
 - Better handling of EOL indicators (#3920)
- Fix so that `gcovr` cleans up all `.gcov` files, even those filtered by command line arguments
- Added compatibility with GCC 4.8 (#3918)
- Added a check to warn users who specify an empty `--root` option (see #3917)
- Force `gcovr` to run with `en_US` localization, so the `gcovr` parser runs correctly on systems with non-English locales (#3898, #3902).
- Segregate warning/error information onto the `stderr` stream (#3924)
- Miscellaneous (Python 3.x) portability fixes
- Added the master svn revision number as part of the version identifier

4.8 2.3.1 (6 January 2012)

- Adding support for Python 3.x

4.9 2.3 (11 December 2011)

- Adding the `--gcov-filter` and `--gcov-exclude` options.

4.10 2.2 (10 December 2011)

- Added a test driver for `gcovr`.
- Improved estimation of the `<sources>` element when using `gcovr` with filters.
- Added revision and date keywords to `gcovr` so it is easier to identify what version of the script users are using (especially when they are running a snapshot from trunk).
- Addressed special case mentioned in [comment:ticket:3884:1]: do not truncate the reported file name if the filter does not start matching at the beginning of the string.

- Overhaul of the `--root / --filter` logic. This should resolve the issue raised in #3884, along with the more general filter issue raised in [comment:ticket:3884:1]
- Overhaul of gcovr's logic for determining gcc/g++'s original working directory. This resolves issues introduced in the original implementation of `--object-directory` (#3872, #3883).
- Bugfix: gcovr was only including a `<sources>` element in the XML report if the user specified `-r` (#3869)
- Adding timestamp and version attributes to the gcovr XML report (see #3877). It looks like the standard Cobertura output reports number of seconds since the epoch for the timestamp and a dotted decimal version string. Now, gcovr reports seconds since the epoch and "gcovr ``"+`__version__` (e.g. "gcovr 2.2") to differentiate it from a pure Cobertura report.

4.11 2.1 (26 November 2010)

- Added the `--object-directory` option, which allows for a flexible specification of the directory that contains the objects generated by gcov.
- Adding fix to compare the absolute path of a filename to an exclusion pattern.
- Adding error checking when no coverage results are found. The line and branch counts can be zero.
- Adding logic to process the `-o/--output` option (#3870).
- Adding patch to scan for lines that look like:

```
creating `foo'
```

as well as

```
creating 'foo'
```

- Changing the semantics for EOL to be portable for MS Windows.
- Add attributes to xml format so that it could be used by hudson/bamboo with cobertura plug-in.

4.12 2.0 (22 August 2010)

- Initial release as a separate package. Earlier versions of gcovr were managed within the 'fast' Python package.

CHAPTER 5

License

Copyright 2013-2018 the gcovr authors

Copyright 2013 Sandia Corporation. Under the terms of Contract DE-AC04-94AL85000 with Sandia Corporation, the U.S. Government retains certain rights in this software.

Gcovr is available under the 3-clause BSD License. See LICENSE.txt for full details. See AUTHORS.txt for the full list of contributors.

Gcovr development moved to this repository in September, 2013 from Sandia National Laboratories.

Symbols

- exclude-directories <exclude_dirs>
gcovr command line option, 12
- exclude-unreachable-branches
gcovr command line option, 12
- fail-under-branch <min>
gcovr command line option, 11
- fail-under-line <min>
gcovr command line option, 11
- gcov-exclude <gcov_exclude>
gcovr command line option, 12
- gcov-executable <gcov_cmd>
gcovr command line option, 12
- gcov-filter <gcov_filter>
gcovr command line option, 12
- gcov-ignore-parse-errors
gcovr command line option, 12
- html
gcovr command line option, 11
- html-absolute-paths
gcovr command line option, 12
- html-details
gcovr command line option, 12
- html-encoding <html_encoding>
gcovr command line option, 12
- html-high-threshold <high>
gcovr command line option, 11
- html-medium-threshold <medium>
gcovr command line option, 11
- html-title <title>
gcovr command line option, 12
- object-directory <objdir>
gcovr command line option, 13
- source-encoding <source_encoding>
gcovr command line option, 11
- version
gcovr command line option, 11
- xml-pretty
gcovr command line option, 11

- b, -branches
gcovr command line option, 11
- d, -delete
gcovr command line option, 13
- e <exclude>, -exclude <exclude>
gcovr command line option, 12
- f <filter>, -filter <filter>
gcovr command line option, 12
- g, -use-gcov-files
gcovr command line option, 12
- h, -help
gcovr command line option, 11
- j <gcov_parallel>
gcovr command line option, 13
- k, -keep
gcovr command line option, 13
- o <output>, -output <output>
gcovr command line option, 11
- p, -sort-percentage
gcovr command line option, 11
- r <root>, -root <root>
gcovr command line option, 11
- s, -print-summary
gcovr command line option, 12
- u, -sort-uncovered
gcovr command line option, 11
- v, -verbose
gcovr command line option, 11
- x, -xml
gcovr command line option, 11

G

- gcovr command line option
 - exclude-directories <exclude_dirs>, 12
 - exclude-unreachable-branches, 12
 - fail-under-branch <min>, 11
 - fail-under-line <min>, 11
 - gcov-exclude <gcov_exclude>, 12
 - gcov-executable <gcov_cmd>, 12
 - gcov-filter <gcov_filter>, 12

- gcov-ignore-parse-errors, 12
- html, 11
- html-absolute-paths, 12
- html-details, 12
- html-encoding <html_encoding>, 12
- html-high-threshold <high>, 11
- html-medium-threshold <medium>, 11
- html-title <title>, 12
- object-directory <objdir>, 13
- source-encoding <source_encoding>, 11
- version, 11
- xml-pretty, 11
- b, -branches, 11
- d, -delete, 13
- e <exclude>, -exclude <exclude>, 12
- f <filter>, -filter <filter>, 12
- g, -use-gcov-files, 12
- h, -help, 11
- j <gcov_parallel>, 13
- k, -keep, 13
- o <output>, -output <output>, 11
- p, -sort-percentage, 11
- r <root>, -root <root>, 11
- s, -print-summary, 12
- u, -sort-uncovered, 11
- v, -verbose, 11
- x, -xml, 11
- search_paths, 11

P

Python Enhancement Proposals

- PEP 8, 16

S

search_paths

- gcovr command line option, 11